

BOX RLF 560 T6 0,75kW (241620186)

GENERAL DATA



BACKWARD CURVED CENTRIFUGAL FAN IN SOUNDPROOF CABINET 400°C/2H

MANUFACTURING FEATURES

- Box manufactured in galvanised steel sheet.
- Circular inlet flange.
- Backward impeller with self-cleaning system, direct coupling motor.
- Standard asynchronous squirrel-cage motor with IP-55 protection and Class H insulation type 400°C/2h .
- Manufactured with standard voltages: 400V(Y) 50Hz in three phase motors up to 3kW and 400V(D) 50Hz for higher powers and 400V for 2 speed motors.
- Exchangeable pannels
- Open drive.


APPLICATIONS

Designed for inline installation, they are suitable for:

- Air renewal in buildings and industries.
- Maximum working temperature: 60°C.
- Removing smoke in case of fire. The motor inside the hazardous area (400 ° C / 2 h)

Official homologation by the European laboratory APPLUS according to EN 12101-3:2015
Certification Nr: 0370-CPR-0582

PERFORMANCE CURVE




TECHNICAL DATA


Fan							
RPM	925	Approx. weight	176 kg	Max. Flow	8680 m³/h		
Motor							
Power	0,75 kW	RPM	925	I max. (400V)	1,95 A	Size	90S
Approx. weight	19 kg	Efficiency (%)	76 %	FP	0.73		

ERP DATA

Fan data sheet		
Fan type	Unit for non-residential ventilation (LOT 6)	
Typology	Unidirectional	
reports.other	None	
Type of driver	None	
Motor power (kW)	0.75	
	Fan values	ERP Requirements 2018
Max. efficiency (%)	52.52	40.5
Effic. Heat recovery (%)	-	
Pabs (kW)	0.785	
Flow (m³/h)	5304.94	
Static pressure (Pa)	264.97	
Speed (m/s)	6.25	
SFP (W/m³/s)	532.81	




DIMENSIONS




Dimensions (mm)									
A	925	B	925	C	925	D	821	E	753
G	74	H	1127	J	1077	K	753	L	683
ØF	548								

WIRING DIAGRAM

230V 



400V 



ACCESSORIES



SAFETY SWITCH
INT 25 3P A
REF: INT253PA



ANTI-VIBRATING FLANGE 400²/2H
BA-400 56
REF: 960002056



ANTI-VIBRATION JOINT
JE 45
REF: A-300719201



INLET/OUTLET ROUND COVER
TIAC 56
REF: 960001956



CIRCULAR SILENCER
SIL-C 560/560
REF: 960056056



CIRCULAR SILENCER
SIL-C 560/840
REF: 960056084



CIRCULAR SILENCER
SIL-C 560/1120
REF: 960056112



CIRCULAR SILENCER
SIL-CN 560/560
REF: 961056056



CIRCULAR SILENCER
SIL-CN 560/840
REF: 961056084



CIRCULAR SILENCER
SIL-CN 560/1120
REF: 961056112




SAFETY SWITCH FOR 400°C/2h
INT 400 25A 3P
REF: 508902501



FREQUENCY SPEED CONTROLLER
SFC 400 III 2,2A *
REF: SFC400III2

SPARE PARTS



	Code	Model	Qty
3	721881250	MOTOR 0,75KW T6 B3 400G	x1
4	960003215	FLANGE AC-560	x1