

NIMUS 311 T4 0,37kW (std) (NS311471)

GENERAL DATA



CENTRIFUGAL FAN, FOR CLEAN OR SLIGHTLY DUSTY AIR

MANUFACTURING FEATURES

- Medium pressure centrifugal fan with direct coupling.
- Reinforced housing made of carbon laminated steel, protected against corrosion by powder coating polyester resin RAL 5010. Finish C3.
- Casing fully latched and adjustable.
- Self-cleaning turbine and reinforced impeller with high-performance backward (reaction) blades made of carbon laminated steel dynamically balanced to minimize noise and vibrations. Black painted RAL 9005
- Squirrel cage standardized asynchronous IEC motor with IP-55 protection and class F electrical insulation. Standard voltages 230/400V 50Hz for three-phase motors up to 4kW and 400/690V 50Hz for higher powers. IE4 motors for 75kW power or higher.
- Motor with feet (B3) supported on motor support foot.
- Models of size 500 and above are supplied with a front support foot, for the other models the front support foot is optional.
- Maximum working temperature in continuous: air transported: 130°C, Environment: 60°C.
- Available positions (to be indicated in case of order): LG270, LG0, LG45, LG90, LG135, LG180, LG225, LG315, RD0, RD45, RD90, RD135, RD180, RD225, RD270, RD315.
- The indicated codes correspond to the model in position LG270

APPLICATIONS


Suitable for moving clean or dusty air. Designed to be installed in conduit for suction or impulsion.

- Paint booths
- Collection of dust
- Food industry dryers
- Food processing
- Incineration
- Odor control in industry
- Indoor / outdoor pollution control
- Big buildings
- Malls
- Factories / Industrial buildings
- Warehouses
- Extraction of smoke
- Boilers and ovens
- Manufacture and treatment of chemical products.
- Tunnels, underground stations.

ON DEMAND

- Fans for special voltages.
- 2 speed motor.
- C4 or C5 coating painting
- Hot dip galvanized
- Inox 304 (normal or electropolished finish)
- Inox 316 (normal or electropolished finish)
- Cooling wheel
- Anticaloric paint
- Fully welded housing (waterproof)
- Inspection door to facilitate maintenance and cleaning
- Drain plug.
- Airtight axle
- Non-sparking air passage and standard motor
- Other brands of motors.

PERFORMANCE CURVE




TECHNICAL DATA


Fan							
RPM	1370	Approx. weight	40.7 kg	Max. Flow	2360 m³/h		
Motor							
Power	0,37 kW	RPM	1370	I max. (230V)	1,86 A	I max. (400V)	1,07 A
Size	71	Approx. weight	6.2 kg	Efficiency (%)	69.5 %		

ERP DATA

Fan data sheet			350
Fan type	Centrifugal fan backward blades with casing		
Installation category	A: Outlet and Inlet free discharge		
Efficiency category	Static		
The fan has to be installed with VF	No		
Motor power (kW)	0.37		150
	Fan values	ERP Requirements 2015	
Max. efficiency (%)	44.86	43.51	50
Efficiency grade (N)	62.35	61	
Pabs (kW)	0.216		
Flow (m³/h)	1359.99		
Static pressure (Pa)	252.98		
Speed (m/s)	1370		
Specific ratio	1.00		



DIMENSIONS




Dimensions (mm)									
A1	396	A2	260.7	B1	241.3	B2	314.1	C1	234
C2	450.6	C3	340.8	C4	287.4	C5	35	D	354.5
D1	11.5	D2	20	E	558.9	F (±)	441.5	G (±)	207
H	35.5	HC	415.6	I	289	J	324	K	313.5
L	200	M	79	N	278	N1	198	N2	248

Dimensions (mm)

O	90	P	95	Q	272.9	R	395	R1	315
R2	365	S	344	T	430	U	69.3	V	26.3
W	344.6	X	71	Y	M8	Z	8holes x45°		

WIRING DIAGRAM



ACCESSORIES



SAFETY SWITCH
INT 25 3P A
REF: INT253PA



ANTI-VIBRATING FLANGE 400°/2H
BA-400 30/31
REF: 960002052



CONNECTION FLANGE
AC 300
REF: 960003209



CIRCULAR-CIRCULAR ANTI-VIBRATION FLANGE FOR STORM
BADS 315
REF: BADS-3131



RECTANGULAR-RECTANGULAR ANTI-VIBRATION FLANGE FOR STORM
BIDS 198x315-200
REF: BIDS-31198



FREQUENCY SPEED CONTROLLER
SFC 400 III 1,2A *
REF: SFC400III1



INLET PROTECTION GUARD FOR CENTRIFUGAL FANS
RA 31/12
REF: A-253451901



ANTI-VIBRATION JOINT
JE 45
REF: 300719201



OUTLET FLANGE FOR STORM MODELS
EIS 315x198-315
REF: EIS-3119831



OUTLET PROTECTION GUARD FOR STORM FANS
RIS 315x198
REF: RIS-31198E2



FREQUENCY SPEED CONTROLLER
SFC 230 I 2,5A *
REF: SFC230I003



ANTI-VIBRATION RUBBER BLOCK
AVR (GENERIC)



ANTI-VIBRATION SPRING BLOCK
AVS (GENERIC)



FRONTAL FEET SUPORT
CPD-N31
REF: A-CPD-N31



ACOUSTIC CABINS FOR CENTRIFUGAL FANS
AB (GENERIC)



MULTIPOSITION FRONTAL FEET SUPPORT
CPDMP-N31
REF: A-CPDMP-N31

SPARE PARTS

	Code	Model	Qty
1	R-BAD-N31	INLET CONE 315	x1
2	721001131WEG	MOTOR 0,37KW IE3 4P B3	x1
3	721001131WEG	MOTOR 0,37KW IE3 4P B3	x1