


PRESTUR 711 T4 7,5kW (std) (PS7114132)

GENERAL DATA



MEDIUM PRESSURE FAN FOR PAINT BOOTHS

MANUFACTURING FEATURES:

- Medium pressure centrifugal fan with direct coupling.
- Reinforced housing made of carbon laminated steel, protected against corrosion by powder coating polyester resin RAL 5010. Finish C3.
- Casing fully latched and adjustable.
- Self-cleaning turbine and reinforced impeller with high-performance backward (reaction) blades made of carbon laminated steel dynamically balanced to minimize noise and vibrations. Black painting RAL 9005
- Squirrel cage standardized asynchronous IEC motor with IP-55 protection and class F electrical insulation. Standard voltages 230/400V 50Hz for three-phase motors up to 4kW and 400/690V50Hz for higher powers.
- Motor with flange (B5), airtight axle
- Double suction flange
- Maximum working temperature in continuous: transported air: 130°C, ambient: 60°C.
- Available positions (to be indicated in case of order): LG and RD
- The indicated codes correspond to the model in position LG

APPLICATIONS


Suitable for moving clean or dusty air. Designed to be fixed in the double suction flange, with the motor in vertical position.

- Paint booths
- Collection of dust
- Food industry dryers
- Food processing
- Incineration
- Odor control in industry
- Indoor / outdoor pollution control
- Big buildings
- Malls
- Factories / Industrial buildings
- Warehouses
- Extraction of smoke
- Boilers and ovens
- Manufacture and treatment of chemical products.
- Tunnels, underground stations.

ON DEMAND

- Fans for special voltages.
- 2 speed motor.
- C4 or C5 coating painting
- Hot dip galvanized
- Inox 304 (normal or electropolished finish)
- Inox 316 (normal or electropolished finish)
- Cooling wheel
- Anticaloric paint
- Fully welded housing (waterproof)
- Inspection door to facilitate maintenance and cleaning
- Drain plug.
- Non-sparking air passage and standard motor
- Other brands of motors.

PERFORMANCE CURVE




TECHNICAL DATA

Fan							
RPM	1455	Approx. weight	308 kg	Max. Flow	26990 m³/h		
Motor							
Power	7,5 kW	RPM	1455	I max. (400V)	14,1 A	I max. (690V)	8,17 A
Size	132M	Approx. weight	68 kg	Efficiency (%)	90.4 %	FP	0.86


ERP DATA

Fan data sheet		
Fan type	Centrifugal fan backward blades with casing	
Installation category	A: Outlet and Inlet free discharge	
Efficiency category	Static	
The fan has to be installed with VF	No	
Motor power (kW)	7.5	
	Fan values	ERP Requirements 2015
Max. efficiency (%)	74.57	59.71
Efficiency grade (N)	75.86	61
Pabs (kW)	7.542	
Flow (m³/h)	15211.03	
Static pressure (Pa)	1311.61	
Speed (m/s)	1455	




	Fan values	ERP Requirements 2015
Specific ratio	1.01	

DIMENSIONS



Dimensions (mm)									
A1	487.5	A2	692.8	A3	452	B1	843.7	B2	572.4
B3	813.2	D	448.7	E	826	F	755	G	1051.3
J	408.3	K	458	L	185	M	184.5	N	529
N1	449	O	210	P	210	R	790	R1	710
aº	11,25º	nºholes	16x22,5º						

WIRING DIAGRAM



ACCESSORIES



SAFETY SWITCH
INT 25 3P A
REF: INT253PA




CONNECTION FLANGE
AC 710
REF: 960003217



ANTI-VIBRATION JOINT
JE 45
REF: 300719201



CIRCULAR-CIRCULAR ANTI-VIBRATION FLANGE FOR STORM
BADS 710
REF: BADS-7171



OUTLET BEND FOR STORM FANS
CPS 710x449-710
REF: CPS-7144971



FREQUENCY SPEED CONTROLLER
SFC 400 III 16A *
REF: SFC400III16



ANTI-VIBRATION SPRING BLOCK
AVS (GENERIC)



INLET PROTECTION GUARD FOR CENTRIFUGAL FANS
RA 71/22
REF: A-243711901



ANTI-VIBRATING FLANGE 400°/2H
BA-400 71
REF: 960002058



OUTLET FLANGE FOR STORM MODELS
EIS 710x449-710
REF: EIS-7144971



OUTLET PROTECTION GUARD FOR STORM FANS
RIS 710x449
REF: RIS-71449E2



RECTANGULAR-RECTANGULAR ANTI-VIBRATION FLANGE FOR STORM
BIDS 449x710-200
REF: BIDS-71449



ANTI-VIBRATION RUBBER BLOCK
AVR (GENERIC)



ACOUSTIC CABINS FOR CENTRIFUGAL FANS
AB (GENERIC)



SPARE PARTS

	Code	Model	Qty
1	R-BAD-N71	INLET CONE 710	x1
2	721001192	MOTOR 15KW IE3 4P B5	x1
3	721001185	MOTOR 7,5kW T4 B5 400/690V	x1